

TECHNICAL DATA SHEET - CONCRETE SPACER

DESCRIPTION

Concrete spacer with three cover layers for both horizontal and vertical reinforcement. Available with or without fixed galvanized wire.
Note that there is no hole in the spacers without wire.

Concrete strength: > 60 N/mm²

For mix design requirements, use Concretespacer in mix StQ3 + see more information here:



<https://haucon.dk/forbrugsartikler/afstandsholdere-til-armering/beton/betonafstandsklods-stq3>

GEOMETRY



Article no.	Description	Cover layer
1131500	Betonafstandsklods u/tråd	20/25/30
1131505	Betonafstandsklods m/tråd	20/25/30
1131510	Betonafstandsklods u/tråd	35/40/50
1131520	Betonafstandsklods m/tråd	35/40/50
1131525	Betonafstandsklods u/tråd	45/55/60
1131530	Betonafstandsklods m/tråd	45/55/60

NOTE:

The above variants are stock items. All designs of concrete spacers in HauCon's range can be produced in mix-design StQ1 or StQ3+.

A production time of 4 weeks must be expected for non-stocked types.

ENVIRONMENTAL CLASS

X0, XC1, XC2, XC3, XC4, XA1, XD1, XS1, XS2, XF2, XF3 XA2, XD2, XD3

CE-MARKING

Concrete spacers are not subject to a harmonized standard and therefore do not have to be CE marked according to the Building Products Regulation No. 305/2011.

Note: We take reservations for typing errors and refer to the current version of data is always available at www.haucon.dk or can be requested by contacting the expedition. Current revision number is stated at the top left corner.