

TECHNICAL DATASHEET - HC-BINDETRÅD BTD

Tie wire in handsize coils.

BTB 1,5: app. 14,4 m/roll and app. 100 rolls/bucket.
BTB 1,7: app. 10,6 m/oll and app. 100 rolls/bucket.

Steel quality EN 10016-2 C9D

DIN 10204/3.1



MECHANICAL COMPOSITIONS - MELTING ANALYSIS (WEIGHT %)

MELT NO.	C %	Mn %	Si %	P %	S %	Cu %	Ni %	Cr %	Mo %	V %	N %	Al %
1VF2505010	0,04	0,28	0,05	0,01	0,006	0,14	0,07	0,04	0,01	0,01	0,002	0,008
1VF2505013	0,03	0,29	0,06	0,009	0,004	0,18	0,07	0,06	0,01	0,009	0,002	0,009
1VF2505011	0,04	0,31	0,04	0,01	0,007	0,2	0,1	0,05	0,01	0,009	0,009	0,008
1VF2506214	0,03	0,27	0,06	0,009	0,007	0,13	0,07	0,04	0,01	0,01	0,002	0,01

VARIANTS

DESCRIPTION	SIZE	WIRE TYPE	PACKAGING
HC-Bindetråd BTB 1,5 mm	1,50 mm	Sort	20 kg
HC-Bindetråd BTB 1,7 mm	1,70 mm	Sort	20 kg

CE-MÆRKNING

HC-Bindetråd BTB is not subject to a harmonized standard and therefore does not have to be CE marked according to the Building Products Regulation No. 305/2011.