

DECLARATION OF PERFORMANCE

Annex III of the Regulation (EU) No 305/2011

No. of DoP: GCPAT-MI-3062-02

1. Unique identification code of the product-type:

EN 13967 - Type T

2. Type, batch or serial number or any other element allowing identification of the construction product as required pursuant to Article 11(4):

Batch No. see packaging of the product

3. Intended use or uses of the construction product, in accordance with the applicable harmonised technical specification, as foreseen by the manufacturer:

Plastic waterproofing sheet for basements

4. Name, registered trade name or registered trade mark and contact address of the manufacturer as required pursuant to Article 11(5):

**Menkol Industries PVT LTD,
Kinfra Industrial And Textile Park, Kanjikode, Palakkad, Kerala, India 678621**

5. Where applicable, name and contact address of the authorised representative whose mandate covers the tasks specified in Article 12(2):

**SAINT-GOBAIN CONSTRUCTION CHEMICALS
GCP Germany GmbH
Pyrmonter Str. 56
32676 Lügde Germany**

6. System or systems of assessment and verification of constancy of performance of the construction product as set out in Annex V:

**EN 13967:2012
System 2+**

7. In case of the declaration of performance concerning a construction product covered by a harmonised standard:

The notified body DEDAL, identification number 1922 performs the continuous surveillance, assessment and evaluation of the factory production control under system 2+ and issued a certificate of conformity of the Factory Production Control 1922-CPR-1854

8. In case of the declaration of performance concerning a construction product for which a European Technical Assessment has been issued:

Not applicable

9. Declared Performance

Characteristics	Performance	Test Method	Harmonized Technical Specification EN 13967:2012 Paragraph
Visible defects	None	EN 1850-2	5.3
Straightness	Pass	EN 1848-2	5.4
Length (m)	20±0.25 10±0.25	EN 1848-2	
Thickness (mm)	1.2 ± 0.07	EN 1849-2	
Width of Carrier Sheet (mm)	1200 ± 10	EN 1848-2	
*Water tightness to liquid water (at 60 kPa)	Pass	EN 1928	5.6
*Resistance to impact (AI-board) (mm)	≥ 150	EN 12691	5.7
*Durability of water tightness against ageing/degradation (at 60 kPa)	Pass	EN 1296 EN 1928 Method B	5.8
*Durability of water tightness against chemicals (at 60 kPa)	Pass	EN 1847 EN 1928 Method B	
Compatibility with bitumen	Pass	EN 1548 EN 1928	5.9
*Resistance to tearing (Nail Shank) (N)	≥ 375	EN 12310-1	5.10
*Joint strength (N/50 mm)	≥ 450	EN 12317-2	5.11
Water vapour transmission (μ =sD/d)	750,000 ± 30%	EN 1931	5.12
*Resistance to static loading (kg)	≥ 20 - Pass	EN 12730	5.13
*Tensile properties – unreinforced sheets (Maximum tensile force in N/50 mm)	Long ¹ ≥ 500 Trans ² ≥ 500	EN 12311-2 Method A	5.14
*Tensile properties – unreinforced sheets (Elongation at maximum tensile force in %)	Long ¹ ≥ 4 Trans ² ≥ 4	EN 12311-2 Method A	
Resistance to deformation under load	NPD ³	As relevant	5.15
*Reaction to fire (class)	E	EN 13501-1	5.16
*Dangerous Substances	NPD ³	As relevant	5.17

Footnotes: 1. Longitudinal – related to the roll direction, 2. Transversal to the roll direction, 3. NPD: No performance determined.

*Essential Property Annex ZA, Table ZA.1

10. The performance of the product identified in points 1 and 2 is in conformity with the declared performance in point 9.
This declaration of performance is issued under the sole responsibility of the manufacturer identified in point 4.

Signed for and on behalf of the manufacturer by:

Quality Manager

Cyriel
CYRIEL

Place PALAKKAD

Date

10/06/2025

