

TECHNICAL DATASHEET - FIBERSLANGE

DESCRIPTION

Fiberslange with knobs for horizontal reinforcement.
Turns as shown in the picture, and is displaced in the casting direction.

Concrete strength: 35-45 N/mm²

For mix design requirements, please use **Beton Zig-Zag in mix design StQ3+**
more information: <https://haucon.dk/produkt/beton-zig-zag-stq3/>



GEOMETRY

Length: 80 cm.

Item no.	Description	Concrete cover
1121220	Fiberslange 25 mm	25 mm
1121225	Fiberslange 30 mm	30 mm
1121230	Fiberslange 35 mm	35 mm
1121235	Fiberslange 40 mm	40 mm
1121236	Fiberslange 45 mm	45 mm
1121240	Fiberslange 50 mm	50 mm
1121241	Fiberslange 55 mm	55 mm
1121242	Fiberslange 60 mm	60 mm

CE-MARKNING

Fiberslange is not subject to a harmonized standard and must therefore not be CE marked according to the Building Products Regulation No. 305/2011.

ENVIRONMENTAL CLASS

X0, XC1, XC2, XC3, XC4, XF1, XA1, XD1, XF2, XF3 XA2, XD2, XF4

Note: We take reservations for typing errors and refer to the current version of data is always available at www.haucon.dk or can be requested by contacting the expedition. Current revision number is stated at the top left corner.