

Preprufe® SC1

Non-bituminous, quick drying, damp and green concrete tolerant solvent based primer for use with Preprufe 800PA cold applied, self adhesive waterproof membrane

Description

Preprufe® SC1 is a green coloured, non-bituminous, solvent based primer, which provides good initial adhesion of Preprufe 800PA non-bituminous adhesive membrane.

Use

Used to prime concrete surfaces, including “green” concrete or damp to touch substrates, as well as wood surfaces, on which Preprufe® 800PA membrane will be applied. Preprufe SC1 can be used on vertical and horizontal applications at -5 °C or above.

Application

Preprufe SC1 may be applied by a roller or brush. Apply it to clean, dirt free, frost-free surfaces at a coverage rate of 10-12 m² per litre. Allow the primer to dry 30 minutes or until tack-free. Dry time may be longer in cold temperatures. Deep puddles of primer should be avoided as this will lengthen drying time. Do not apply directly to Preprufe 800PA membrane.

In general, priming should be limited to an area that can be covered with membrane within 24 hours. Areas that accumulate significant amounts of dust or dirt must be re-primed before membrane is applied.

Advantages

- Quick drying - fast membrane application.
- Damp and green concrete tolerant.
- Active formulation for enhanced membrane adhesion.
- Compatible with Preprufe 800 PA membrane.
- Green colour to ensure proper coverage and to aid identification, and to avoid substitution.

Supply

Preprufe SC1	5 & 20 litre can
Coverage	10-12 sq m per litre*

* Depending upon method of application, surface porosity and ambient temperature.

Typical Properties

Property	Typical Value
Colour	Green
VOC	592 g/L
Curing at 20 °C	30 minutes

All declared values shown in this data sheet are based on test results determined under laboratory conditions and with the product sample taken directly from stock in its original packing without any alteration or modification of its component parts.

Health and Safety

Preprufe SC1 must be handled properly and stored in well ventilated place. Read the product label and Safety Data Sheets before use. Users must comply with all risk and safety phrases. SDS's can be obtained from GCP Applied Technologies or from our web site at gcpat.com.